

MODEL N-4I ALU

ENG

Manual hand pumps:

Are always a useful and cost effective alternative to conventional electric or air operated drum pumps when only small quantities of media have to be removed out of canisters or drums or if the customer would use the drum pump only occasionally or rarely.

Electric or air operated drum and container pumps:

Drum and container pumps consist of a high-performance, internally or externally ventilated universal motor, which is also available in an explosion-proof version and a pump tube that is suitable for the application.

The pump tubes of drum pumps are available in PP, PVDF, ALUMINIUM, SS 316.



MAIN FEATURES

ALUMINIUM (Alu)

Are suitable for neutral and hardly combustible liquids.

With these pump tubes particularly mineral oil products up to a maximum viscosity of 1,000 mPas will be transferred.

Drive shaft: Stainless steel 316

Media temperature: max. 90 °C.

Aluminium pump tubes

Drive shaft made of stainless steel AISI 316.

Hose connection 1" included.

Maximum medium temperature 90 °C.

STANDARD TUBE LENGTHS

700 mm | 1000 mm | 1200 mm


ALUMINIUM WITH STAINLESS STEEL DRIVE SHAFT AISI 316

Pump tube diameter	Pump tube length	Version	Code
Ø 41 mm	700 mm	Rotor	24410070
Ø 41 mm	1000 mm	Rotor	24410100
Ø 41 mm	1200 mm	Rotor	24410120

AXIAL ROTOR

Standard in all pump tubes

Pump tubes with rotor are used when high capacities and low heads are required.



SPECIAL LENGTHS ARE AVAILABLE ON REQUEST



CASPANI NUOVE TECNOLOGIE

Montano Lucino CO - Via dell'Industria 3a

Tel 031/471714 Fax 031/470351

www.cntcaspani.com