

## MODEL N-4I PVDF

### ENG

#### Manual hand pumps:

Are always a useful and cost effective alternative to conventional electric or air operated drum pumps when only small quantities of media have to be removed out of canisters or drums or if the customer would use the drum pump only occasionally or rarely.

#### Electric or air operated drum and container pumps:

Drum and container pumps consist of a high-performance, internally or externally ventilated universal motor, which is also available in an explosion-proof version and a pump tube that is suitable for the application.

The pump tubes of drum pumps are available in PP, PVDF, ALUMINIUM, SS 316.



### MAIN FEATURES

#### POLYVINYLIDENFLUORIDE (PVDF)

Are especially suitable for highly aggressive liquids such as concentrated acids and bases.

Drive shaft: Hastelloy 2,4610

Media temperature: max. 90 °C.

#### PVDF pump tubes

Drive shaft made of hastelloy 2,4610.

Hose connection 1" included.

Maximum medium temperature 90 °C.

### STANDARD TUBE LENGTHS

700 mm | 1000 mm | 1200 mm

## PVDF WITH HASTELLOY DRIVE SHAFT 2,4610

Pump tube diameter	Pump tube length	Version	Code
Ø 41 mm	700 mm	Rotor	23410070
Ø 41 mm	1000 mm	Rotor	23410100
Ø 41 mm	1200 mm	Rotor	23410120

### AXIAL ROTOR

#### Standard in all pump tubes

Pump tubes with rotor are used when high capacities and low heads are required.



SPECIAL LENGTHS ARE AVAILABLE ON REQUEST