

MODEL TY6

ENG

TYPHOON vertical centrifugal pumps are high performance pumps for fixed installations with the pump immersed directly in the tank. These pumps are used to quickly empty the fluid, with flow rates ranging from 6 to 40 m³/h. The special semi-opened impeller design, allows continuous pumping even with dirty fluids with apparent viscosity up to 500cps. and small suspended solids. TYPHOON are electric motor driven pumps that, through a flexible coupling, transmitting the rotation to the shaft and the impeller, due to centrifugal effect, creates a suction on the central duct and a delivery on the peripheral tube.

MAIN FATURES

- Casing and impeller in PP and PVDF
- O-ring in EPDM and VITON
- Lenght from 250mm to 1400mm
- Max delivery head 25 mts
- Max flow - Rate: 40 m³/h
- Temperature: from -20°C to +95°C
- Max viscosity: 500 CPS
- Electric motors from 0,37 Kw up to 5,5kW
- Specific Gravity up to 1.9

TECHNICAL DATA

Inlet connections	1" 1/2 F
Outlet connections	1" M
Max. Flow rate	6 m ³ /h
Max. Delivery head	8 mts
Max Viscosity	100 cps
Temperature PP	-5°C +65°C
Temperature PVDF	-20°C +95°C
Impeller	Semi-Opened

PP



PVDF




INSTALLATION

DRY RUNNING

Suitable devices should be fitted to prevent dry running and the formation of a vortex and possible air suction. Running dry or with air bubbles can cause damage to the pump.

PERFORMANCE



The curves and performance values refer to pumps with free delivery outlet with water at 20 °C, and two poles motor 50 Hz. These data may vary according to the construction materials and hydraulic conditions.


MOTOR SPECIFICATION

SIZE	Kw	DESIGN
IEC 71	0,37	B5
IEC 71	0,55	B5
IEC 71	0,75	B5

SPECIFIC GRAVITY TABLE

L = 0,37 Kw	M = 0,55 Kw	H = 0,75 Kw
up to 1,2	up to 1,5	up to 1,9

DIMENSIONS



A	B	C	D	E	F	G	H	I	M	N	O	P
*	147	20	80	340	130	128.5	81.5	260	290	130	210	Ø165

*Depend on the manufacturer

COMPOSITION

MODEL	CASING	O RING	LENGHT mm	CONNECTIONS	PUMP DESIGN	MOTOR VERSION
TY006	P = PP K = PVDF	D = EPDM V = VITON	250 500 800	1 = BSP STD 2 = FLANGED	L = LOW DENSITY M = MEDIUM DENSITY H = HIGH DENSITY	IE = IEC FLANGE



CASPANI NUOVE TECNOLOGIE

Montano Lucino CO - Via dell'Industria 3a

Tel 031/471714 Fax 031/470351

www.cntcaspani.com